


Technical Data Sheet

MONOETHYLENE GLYCOL

1,2-ethanediol; Ethylene glycol (MEG)

CAS Number: **107-21-1**

Formula: C₂H₆O₂



DESCRIPTION:

Monoethylene glycol is a clear, colorless and hygroscopic liquid, with moderately viscous. It is completely miscible with water and many organic liquids.

APPLICATION:

Monoethylene glycol (MEG) is most commonly used as chemical intermediate in the manufacture of polyester resins and textile fibers. MEG is also widely used as automotive antifreeze due to its low freezing point when mixed with water and used as heat transfer fluids for ventilation and air-conditioning systems.

PHYSICAL PROPERTIES:

Form	liquid
Appearance	Clear
Molecular Weight	62.07
pH	7
Boiling Point, 760 mm Hg, °C	198
Flash Point, PMCC, °C	111
Freezing Point, °C	-12
Specific Gravity, 20/20°C	1.1153
Conductivity, µS/cm	0.57
Refractive Index, 20°C	1.4321
Vapor Pressure, mm Hg, 20°C	0.06
Viscosity, cSt, 40°C	8.712
Sodium as Na, ppm	<0.1
Potassium as K, ppm	<0.1
Sulfate as SO ₄ ²⁻ , ppm	<1

REGULATORY INFORMATION:

IMDG Classification	Non-Dangerous
	Goods
HMIS Code	2-1-0
HS Code	2905.31.00



HANDLING AND STORAGE:

Keep the material in the anhydrous state to prevent severe corrosion to the carbon steel or aluminum tank and related equipment. For longer term color stability, it is recommended that the product be stored under an inert atmosphere.

Monoethylene glycol products have 24 months of shelf-life time under unopened drum. The product should be re-evaluated after 24 months to reconfirm the product quality, if properly stored and protected from contamination. For bulk container, the shelf-life time of product is 6 months from manufacturing date.

For storage conditions, product is hygroscopic, water contamination should be avoided. Keep container tightly closed without air contamination. Due to Monoethylene glycol is very sensitive with moisture, an elevated moisture level when do re-sampling might be faced. The periods of exposure to high temperatures should be minimized. Avoid directly contact with sunlight and higher temperature. Monoethylene glycol is recommended to be stored under an inert atmosphere such as nitrogen blanket to sustain product stability.

PACKAGING:

Product is available in bulk truck, ISO Tank, flexi bag, IBC tank, steel drum with epoxy phenolic coating. Recommended containers are stainless steel and aluminum or carbon steel with suitably lined. IBC tank material should be HDPE with UV stabilized and opaque to prevent UV degradation. Certain government regulations may apply at the time of shipment and delivery.

SAFETY:

Wear appropriate personal protective equipment, including appropriate respiratory protection. Avoid contact with skin, eyes or clothing. For information on the toxicity and handling of this product, please find in the Material Safety Data Sheet.

TERMS & CONDITIONS:

Copyright © 2016 TOC Glycol Company Limited. All rights reserved.

All information contained in the document is reliable to the best knowledge of TOC Glycol Company Limited. The information is intended to describe the product for the purpose of health, safety and environmental requirements only. All users should conduct an adequate study to firm the suitability of any product in regard to such use. In addition, each user should obtain detailed information on toxicity, handling and storage, proper shipping, together with all appropriate health, safety and environmental standards. No representations or warranties, either express or implied, of merchantability, fitness for a particular purpose or of any other nature are made hereunder with respect to information or the product to which that information refers. In no event will TOC Glycol Company Limited be hereby responsible for loss, damage or expense of any nature whatsoever resulting from the use of or reliance upon the information herein or the product to which that information refers.

TOC Glycol Company Limited

Head Office : 555/1 Energy Complex, Building A,
15th Floor, Vibhavadi Rangsit Road, Chatuchak,
Chatuchak, Bangkok 10900 Thailand.
Tel : +66 (0) 2265 8400
Fax : +66 (0) 2265 8500

Rayong Plant : 9 Soi G12, Hemaraj Eastern Industrial Estate,
Pakorn Songkhraorat Road., Tambon Maptaphut,
Amphoe Mueang Rayong, Rayong 21150, Thailand
Tel : +66 (0) 3899 4000
Fax : +66 (0) 3892 5988

For enquiry, please contact at EOEG@ptgacgroup.com
Technical support engineer: +66(0)3899-4236, +66(0)3899-4584
www.ptgacgroup.com/th/product/eo-base