



9 Soi G 12 Eastern
Industrail Estate, Map Ta
Phut, Muang Rayong
Tel. 6638994000
Fax 66 38977111

SAFETY DATA SHEET

Trade name: MONOETHANOLAMINE

SDS No.001-1

Issued date : 02 May 2013

Rev. 01

1. IDENTIFICATION OF THE SUBSTANCE OR MIXTURE AND OF THE COMPANY/UNDERTAKING

Product identifier:

Substance name: Monoethanolamine

Synonyms: 2-aminoethanol, 2-Amino-1-Ethanol, Ethanolamine, Monoethanolamine, β -Aminoethanol,
 β -hydroxyethylamine, β -Aminoethyl alcohol

Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture

Uses by workers in industrial settings;

Manufacturing of MEA
Formulation of products containing MEA
Industrial use resulting in manufacture of another substance
Processing aid for paper, textile, leather
Gas/water treatment with MEA
Use of MEA in metal working fluids
Use of MEA in electroplating
Use of MEA in detergents, cleaners and ink removers
Use of MEA as additive in plastic, e.g. rubber
Use of MEA as a laboratory chemical
Use of MEA as additive in fuel
Use of fuel
Use of MEA in wood protection formulations

Uses by professional workers;

Use as additive in concrete and cement
Processing aid for paper, textile, leather
Use of MEA in metal working fluids
Use of MEA in detergents, cleaners and ink removers
Use of MEA as additive in plastic, e.g. rubber
Use of MEA as a laboratory chemical
Use of fuel

Uses by Consumers;

Use of concrete and cement



9 Soi G 12 Eastern
Industrial Estate, Map Ta
Phut, Muang Rayong
Tel. 6638994000
Fax 66 38977111

SAFETY DATA SHEET

Trade name: **MONOETHANOLAMINE**

SDS No.001-1

Issued date : 02 May 2013

Rev. 01

Use of fuel

Use of MEA in detergents and cleaners

Use of MEA in wood protection formulations

Use of MEA in personal care products

Uses advised against;

None known

Details of the supplier of the safety data sheet

Address:

TOC Glycol Company Limited

9/1 Soi G12, Hemaraj Eastern Industrial Estate, Pakorn Songkhraorat Road, Tambon Maptaphut, Amphoe Mueang

Rayong, Rayong 21150, Thailand

Telephone no.+66(0)38994000 Ext. 7095

Fax no.+66(0)38925988

Emergency telephone

For medical advice (in Thailand):

+66(0)38994000 Ext. 7095

In case of transport incidents and other emergencies (advice in Thailand):

+66(0)38994000 Ext. 7095

Advice on Safety Data Sheet

Jurelak.c@pttggroup.com

2. HAZARDS IDENTIFICATION

Classification of the substance or mixture

Classification in accordance with Regulation (EC) No 1272/2008 (CLP)

Acute Tox. 4; H302

Acute Tox. 4; H312

Acute Tox. 4; H332

Skin Corr. 1B; H314

STOT SE 3; H335

Classification in accordance with Directive 67/548/EEC or 1999/45/EC

C;R34

Xn;R20/21/22



9 Soi G 12 Eastern
Industral Estate, Map Ta
Phut, Muang Rayong
Tel. 6638994000
Fax 66 38977111

SAFETY DATA SHEET

Trade name: **MONOETHANOLAMINE**

SDS No.001-1

Issued date : 02 May 2013

Rev. 01

Label elements

Labeling according to Regulation (EC) No 1272/2008 (CLP Regulation)

Product identifier

141-43-5 (2-aminoethanol)

Hazard pictograms:



GHS05: Corrosion



GHS07: Exclamation mark

Signal word

อันตราย

Hazard statements

- | | |
|------|---|
| H302 | Harmful if swallowed. |
| H312 | Harmful in contact with skin |
| H314 | Causes severe skin burns and eye damage |
| H332 | Harmful if inhaled. |
| H331 | May cause respiratory irritation. |

Precautionary statements

- | | |
|----------------|--|
| P260 | Do not breathe dust/fume/gas/mist/vapors/spray. |
| P280 | Wear protective gloves/protective clothing/eye protection/face protection. |
| P301/P330/P331 | IF SWALLOWED: rinse mouth. Do NOT induce vomiting. |
| P303/P361/P353 | IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. |
| P304/P340 | IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. |



9 Soi G 12 Eastern
Industrail Estrate, Map Ta
Phut, Muang Rayong
Tel. 6638994000
Fax 66 38977111

SAFETY DATA SHEET

Trade name: **MONOETHANOLAMINE**

SDS No.001-1

Issued date : 02 May 2013

Rev. 01

P305/P351/P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTER or doctor/physician.
P363	Wash contaminated clothing before reuse.
P405	Store locked up.
P501	Dispose of contents/container to hazardous or special waste collection point.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Substance / product identification

Substance name: 2-aminoethanol
CAS no.: 141-43-5
EC no.: 205-483-3
REACH no: 01-2119486455-28-xxxx

Chemical name	Concentration (%)
1. Ethanol,2-amino-	99.00-100.00

4. FIRST AID MEASURES

After inhalation:

If inhaled, remove to fresh air. If not breathing or in respiratory distress, clear person's airway and start artificial respiration. With a physician's advice, give supplemental oxygen using a bag-valve mask or manually triggered oxygen supply.

After skin contact:

Immediately remove contaminated clothing and shoe. Under a safety shoe, flush skin thoroughly with large amounts of running water for at least 15 minutes. Do not attempt to neutralize with chemical agents. Get medical attention immediately. Discard or decontaminate clothing and shoes before reuse.

After eye contact:

Immediately flush eyes with large amounts of running water for at least 15 minutes. Hold eyelids apart while flushing to rinse entire surface of eye and lids with water. Do not attempt to neutralize with chemical agents. Obtain medical attention immediately.



9 Soi G 12 Eastern
Industriail Estrate, Map Ta
Phut, Muang Rayong
Tel. 6638994000
Fax 66 38977111

SAFETY DATA SHEET

Trade name: **MONOETHANOLAMINE**

SDS No.001-1

Issued date : 02 May 2013

Rev. 01

Continue flushing for an additional 15 minutes if medical attention is not immediately available.

After swallowing:

If person is conscious and can swallow, give two glasses of water (16 oz.). Include vomiting as directed by medical personnel. Do not induce vomiting or give anything by mouth to an unconscious or convulsing person.

Other Instruction:

Swallowing of this corrosive material may result in several may result in severe ulceration, inflammation and possible perforation of the upper alimentary tract, with hemorrhage and fluid loss. Aspiration of this product during induced emesis can result in severe lung injury. If evacuation of stomach is necessary, use method least likely to cause aspiration, such as gastric lavage after endotracheal intubation. Contact a Poison Control Center for additional treatment information.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media:

Use water spray, dry chemical, Foam or carbon dioxide to extinguish flames. Use water spray to cool fire-exposed containers. Water or foam may cause frothing.

Special hazards arising from the substance or mixture:

None

Special protective equipment for fire-fighter:

Wear special chemical protective clothing and positive pressure self-contained breathing apparatus. Approach fire from upwind to avoid hazardous vapor and toxic decomposition product. Decontaminate or discard any clothing that may contain chemical residues.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions

Remove persons to safety and ventilate area. Avoid breathing vapor, contacting with skin, eyes or clothing.



9 Soi G 12 Eastern
Industrial Estate, Map Ta
Phut, Muang Rayong
Tel. 6638994000
Fax 66 38977111

SAFETY DATA SHEET

Trade name: **MONOETHANOLAMINE**

SDS No.001-1

Issued date : 02 May 2013

Rev. 01

Environmental precautions

Prevent entry into sewer and waterways

Methods and material for containment and cleaning up

Wear appropriate personal protective equipment, including appropriate respiratory protection. Contain spill if possible. Wipe up or absorb on suitable material and shovel up.

7. HANDLING AND STORAGE

Handling:

Precautions for safe handling

Minimum feasible handling temperatures should be maintained. Eye wash and safety shower should be available nearby when this product is handled or used.

Storage:

Requirement for storage rooms and vessels

Do not use containers, leads, pipes a.s.o. from copper or copper-containing alloys. Do not use zinc containers. Do not use aluminium containers. Reacts above 60°C with aluminium giving off hydrogen gas.

Further information on storage conditions

Periods of exposure to high temperatures should be minimized. Avoid directly contact with sunlight and higher temperature. Keep container tightly closed without air contamination. Product is hygroscopic, water contamination should be avoided.

8. EXPOSURE CONTROLS/ PERSONAL PROTECTION

Exposure limit for the total product:

Monoethanolamine (ethanolamine):	OSHA PEL-TWA 3.0 ppm.	STEL 6.0 ppm
	ACGIH TLV-TWA 3.0 ppm.	STEL 6.0 ppm.

Exposure controls:

Personal protective equipment:



9 Soi G 12 Eastern
Industrial Estate, Map Ta
Phut, Muang Rayong
Tel. 6638994000
Fax 66 38977111

SAFETY DATA SHEET

Trade name: **MONOETHANOLAMINE**

SDS No.001-1

Issued date : 02 May 2013

Rev. 01

Respiratory protection:	Airborne concentrations should be kept to lowest levels possible. If vapor, mist or dust is generated and the occupational exposure limit of the product, or any component of the product, is exceeded, use appropriate NIOSH approved air purifying or air supplied respirator after determining the airborne concentration of the contaminant. Air supplied respirators should always be worn when airborne concentration of the contamination or oxygen content is unknown.
Eye /Face protection:	avoid eye contact. Chemical type goggles should be worn. Do not wear contact lense
Skin protection:	Protective clothing such as coveralls or lab coats must be worn. Launder or dry-clean when soiled. Gloves resistant to chemicals and petroleum distillates required. When handling large quantities, impervious suits, gloves, and rubber boots must be worn. Remove and dry-cleaned or launder clothing soaked or soiled with this material before reuse. Dry cleaning of contaminated clothing may be more effective than normal laundering. Inform individuals responsible for cleaning of potential hazards associated with handling contaminated clothing
Ventilation:	Adequate to meet occupational exposure limits.(See in Exposure limit for The Total Product)

9. PHYSICAL AND CHEMICAL PROPERTIES

Form:	liquid
Color:	Clear liquid
Odor:	ammonia-like
pH value	11.8
Melting point/freezing point	10.5 °C
Boiling temperature	170.5 °C
Flash point	95.5 °C
Flammable limits lower	5
upper	17
Vapor pressure (20 °C)	<1 mmHg at 20 °C
Specific gravity (20 °C)	1.0179



9 Soi G 12 Eastern
Industrial Estate, Map Ta
Phut, Muang Rayong
Tel. 6638994000
Fax 66 38977111

SAFETY DATA SHEET

Trade name: **MONOETHANOLAMINE**

SDS No.001-1

Issued date : 02 May 2013

Rev. 01

Solubility in water(20 °C) > 10

10. STABILITY AND REACTIVITY

Conditions to avoid

Monoethanolamine in contact with iron can form a crystalline complex called tris(ethanolamino)-iron. This compound can ignite when heated to 54-71 °C in the presence of air. For internal steam applications, stainless steel should be used with nitrogen blanket.

This material may react violently with acids. Toxic levels of ammonia, combustion products of nitrogen, carbon dioxide, carbon monoxide, irritating aldehydes and ketones may be formed on burning in a limited air supply.

11. TOXICOLOGICAL INFORMATION

Acute toxicity

LD₅₀ (oral, rat): >1.00- 2.00 g/kg moderately toxic

LD₅₀ (inhalation, rat): none

LD₅₀ (dermal, rabbit): >1.00 g/kg Slightly toxic

Irritation index estimation of irritation (species):

Skin(rabbit) : > 6.50-8.00/8.0 corrosive

Eye irritation test (rabbit): > 80.00-110.00/110 extremely irritation

Sub acute to chronic toxicity :

Prolonged and repeat ingestion of Monoethanolamine has caused kidney damage in laboratory animals. In addition a developmental toxicity study, using unconventional statistical treatment of the data, demonstrated developmental toxicity in rats. The true significances of the study data is not clear, since a full re-interpretation of this data is not possible at this time. Additional or repeat studies are planned or underway to better define the toxic potential of this product, or to verify the results obtained from previous animal studies.



9 Soi G 12 Eastern
Industrial Estate, Map Ta
Phut, Muang Rayong
Tel. 6638994000
Fax 66 38977111

SAFETY DATA SHEET

Trade name: **MONOETHANOLAMINE**

SDS No.001-1

Issued date : 02 May 2013

Rev. 01

12. ECOLOGICAL INFORMATION

Aquatic toxic:

LC50-96 hr Aquatic toxicity rating is >100.00 – 1000.0 ppm. Practically non-toxic.

Mobility:

This product is not expected to be mobile in soil and not be expected to absorb to suspended solids or sediments in water.

Persistence and Biodegradability:

This product undergoes moderate biodegradation and is not expected to be persistent in the environment.

Potential to Bioaccumulate:

This product is not expected to bioaccumulate $K_{ow} = -1.31$

13. DISPOSAL CONSIDERATIONS

Waste disposal method:

This product has been evaluated for RCRA characteristics and does not meet the criteria of a hazardous waste if discarded in its purchased form. Under RCRA, it is the responsibility of the product user to determine at the time of disposal, whether the product meets RCRA criteria for hazardous waste. This is because product uses, transformations, mixtures, processes etc. may render the resulting materials hazardous.



9 Soi G 12 Eastern
Industrail Estrate, Map Ta
Phut, Muang Rayong
Tel. 6638994000
Fax 66 38977111

SAFETY DATA SHEET

Trade name: **MONOETHANOLAMINE**

SDS No.001-1

Issued date : 02 May 2013

Rev. 01

14. TRANSPORT INFORMATION

DOT:

Properly shipping name: Ethanolamine

Hazard Class: 8

Identification number: UN 2491

Packing group: III

Label required: Corrosive



IMDG

Proper shipping name: Ethanolamine

Hazard class: 8

Identification Number: UN 2491

Packing group: III

Label Required: Corrosive

ICAO

Proper shipping name: Ethanolamine

Hazard class: 8

Identification Number: UN 2491

Packing group: III

Label Required: Corrosive

TDG



9 Soi G 12 Eastern
Industrial Estate, Map Ta
Phut, Muang Rayong
Tel. 6638994000
Fax 66 38977111

SAFETY DATA SHEET

Trade name: **MONOETHANOLAMINE**

SDS No.001-1

Issued date : 02 May 2013

Rev. 01

Proper shipping name: Ethanolamine

Hazard class: 8

Identification Number: UN 2491

Label Required: Corrosive

15. REGULATORY INFORMATION

International regulation:

TSCA Inventory Status :

This product, or its components, or are exempt from the Toxic Substance Control Act(TSCA) Chemical Substance Inventory

WHMIS classification:

Class E: Corrosive

Canadian Inventory Status:

This product, or its components, are listed on or are exempt from Canadian Domestic Substance List(DSL)

EINECS Inventory Status:

This product, or its components, are listed on or are exempt from the European Inventory of existing Chemical Substances (EINECS) or the European List of Notified Chemical Substances (ELINCS)

Australian Inventory Status:

This product, or its component, are listed on or are exempt from the Australian Inventory of Chemical Substances (AICS)

Japan Inventory status:

This product, or its components, are listed on or are exempt from the Japan Ministry of International Trade and Industry (MITI) inventory.



9 Soi G 12 Eastern
Industrial Estate, Map Ta
Phut, Muang Rayong
Tel. 6638994000
Fax 66 38977111

SAFETY DATA SHEET

Trade name: **MONOETHANOLAMINE**

SDS No.001-1

Issued date : 02 May 2013

Rev. 01

China Inventory status:

This product, or its components, are listed on or are exempt from the Inventory of Existing Chemical Substances in China (IECSC).

Korea Inventory status:

This product, or its components, are listed on or are exempt from Korea Existing and Evaluated Chemical Substances (KECL) inventory.

New Zealand Inventory status:

This product, or its components, are listed on or are exempt from New Zealand Inventory of Chemicals (NZIoC).

Philippine Inventory status:

This product, or its components, are listed on or are exempt from Philippine Inventory of Chemicals and Chemical Substances (PICCS).

16. OTHER INFORMATION

Further information

The information is based on our current knowledge however it does not represent a guarantee of product properties nor does it create any legal obligation.